



# LED FIXTURE SPECIFICATION

MODEL # **CCS5**



FINAL MODEL #			
PROJECT			
TYPE		AREA	
NOTES			

## STANDARD FEATURES: SCONCE INDOOR

Fixture thermally tested to ensure longevity  
 Maximum light distribution throughout lens  
 Over current/voltage short circuit protection  
 UL and/or CSA Compliant Listed  
 Constant Current Design

FIXTURE	LED ENGINE
<b>BASE</b> CR Steel Construction	<b>LG/NICHIA/SAMSUNG, LED CHIPS</b>
<b>FINISH</b> Solid Bronze Accent	<b>LUMENS PER WATT</b> AVG 100-120 @Module Efficacy
<b>LENS</b> Beige Alabaster Acrylic	<b>KELVIN</b> 27K 30K 35K 40K 50K <b>CRI</b> 80+
<b>LOCATION</b> Damp	<b>DRIVER</b> 120 VOLTS 50/60Hz
<b>COMPLIANT</b> RoHS	<b>POWER FACTOR</b> High
<b>LIFE HOURS</b> 50,000	<b>TRIAC OR ELECTRONIC</b>
<b>WARRANTY</b> Limited 5 Years	Low Voltage Dimming Down To 5% With Wall Box Dimmers
	<b>TESTED</b> LM80 and LM82



### LED LIGHT SOURCE OPTIONS\* ORDERING INFORMATION:

WATTAGE: 12	KELVIN: 3000k	SIZE: 5x2
WATTAGE:	KELVIN:	SIZE:

SIZE OPTIONS
W10 <sup>3/4</sup> H11 <sup>1/2</sup> D4

SYSTEM WATTAGE	2700K WARM WHITE	3000K SOFT WHITE	3500K NEUTRAL	4000K COOL WHITE	5000K DAYLIGHT	LEGACY EQUIVALENT
10/12 DRIVERLESS		1000/1000		1000/1050		CFL 13
14/15 DRIVERLESS		1350/1500		1400/1500		CFL 2 x 13
22/24 DRIVERLESS		1850/2400		1900/2500		CFL 3 x 13
10	1060	1100	1160	1175	1250	CFL 18
12	1265	1360	1405	1460	1560	CFL 2 x 13
16	1650	1700	1720	1750	1800	CFL 2 x 18
20	2100	2140	2180	2200	2250	CFL 2 x 26
24	2570	2740	2830	2950	3150	CFL 2 x 32

\*MORE OPTIONS AVAILABLE UPON REQUEST

## SPECIAL OPTIONS (please specify if applicable)

DRIVER: DVD	FINISH: FCU	LENS: LCU	ACCESSORIES: FUS	TECHNOLOGY: CT
DRIVER:	FINISH:	LENS:	ACCESSORIES:	TECHNOLOGY:

DRIVER	FINISH	LENS	ACCESSORIES	TECHNOLOGY
<input type="checkbox"/> DV 120/277 (Non Dimmable) <input type="checkbox"/> DVD 120/277 (0-10v Dimmable)	<input type="checkbox"/> FB Black <input type="checkbox"/> FBR Bronzestone <input type="checkbox"/> FCU Custom Any RAL Finish <input type="checkbox"/> FSN Satin Nickel <input type="checkbox"/> FW White	<input type="checkbox"/> LCU Custom	<input type="checkbox"/> BBX Back Box (Conduit Holes Optional) <input type="checkbox"/> FUS Fused <input type="checkbox"/> IB Individually Boxed <input type="checkbox"/> PCH Pull Chain <input type="checkbox"/> PS Pin Switch <input type="checkbox"/> SRP Surge Protector	<input type="checkbox"/> CT LED Color Tuning <input type="checkbox"/> EMG Emergency (Any Lumens Package) <input type="checkbox"/> EMGR Emergency Remote <input type="checkbox"/> OS Occupancy Sensor On/Off <input type="checkbox"/> OSCD Occupancy Sensor Step Dimming <input type="checkbox"/> TP Tamper Proof Screws

