




Fixture specification

MODEL # : **CCV30**

STYLE / LAMP / LAMP / WATTAGE / KELVIN / BALLAST / FINISH / LENS / ACCESSORIES / SIZE / COMPLIANCE
QTY TYPE TYPE DETAIL

PROJECT : _____ TYPE : _____ NOTE : _____



FIXTURE FEATURES

- EACH FIXTURE THERMALLY TESTED TO INSURE LONGEVITY
- MAXIMUM LIGHT DISTRIBUTION THROUGHOUT LENS
- OVER CURRENT, OVER VOLTAGE, SHORT CIRCUIT PROTECTION

BASE: STEEL CONSTRUCTION

MOUNTS WITH HOLES AND KNOCKOUTS PROVIDED

END CAP FINISH: BRONZE

LENS: WHITE ACRYLIC
UV STABILIZED
NON-YELLOWING

POWER FACTOR: HIGH
INPUT VOLTAGE: 120V:50/60Hz
COMPLIANCE: CSA LISTED
KELVIN: 3000
CRI: 80
MADE IN AMERICA
DAMP LOCATION

LED LIGHT SOURCE

- LG / NICHIA BRAND LED CHIPS
- CONSTANT CURRENT DESIGNN AVERAGE 100 - 120LPM (LUMEN PER WATT) AT MODULE EFFICACY

- TRIAC OR ELECTRONIC LOW VOLTAGE DIMMING DOWN TO 5% WITH WALL BOX DIMMERS
- DRIVER: UL LISTED
- MODULE: CSA LISTED

- LM80 & LM82 TESTED
- ROHS COMPLIANT
- LIFE HOURS: 50,000
- WARRAANTY: LIMITED 5 YEARS

SYSTEM WATTAGE	LED ENGINE LUMENS				LED'S PER MODULE	LEGACY 30K SUBSTITUTE
	2700K	3000K	3500K	4000K		
13	1014	1083	1130	1165	60	T8 17 / T5 14
19	1351	1444	1506	1553	90	T8 25 / T5 21
21	1622	1508	1808	1864	120	T8 32 / T5 28
24	1824	1696	2033	2096	120	(2) T8 17 / T5 14
39	2482	2587	3120	3198	180	(2) T8 25 / T5 21
44	3300	3069	3679	3793	240	(2) T8 32 / T5 28

SPECIAL OPTIONS

- DRIVER**
- DV 120 / 277 (NON DIMMABLE)
 - DVD 120 / 277 (0-10V DIMMABLE)
 - EMG EMERGENCY
 - EMGR EMERGENCY REMOTE

KELVIN

- 2700K
- 3500K
- 4000K
- 5000K

END CAP FINISH

- 010 BRUSHED NICKEL
- 011 BRUSHED BRASS
- 012 BLACK
- 122 ANTIQUE SILVER

SIZE

- L28" H5" D3-7/8"
- L37" H5" D3-7/8"
- L49" H5" D3-7/8"

For Additional Accessories and Options Visit www.aslighting.com

ASL
25 Twelfth Street
Brooklyn, NY 11215-3820

Toll Free
Phone: 800-369-1101
Fax: 800-552-3465



Local
Phone: 718-369-1100
Fax: 718-369-1105

Online
email: info@aslighting.com
visit: www.aslighting.com

CCV30