




Fixture Specification

MODEL # BCE LED
 STYLE / LIGHT SOURCE / WATTAGE / KELVIN / DRIVER / FINISH / LENS / ACCESSORIES / SIZE / COMPLIANCE / DETAIL



PROJECT : _____ **TYPE :** _____ **NOTE :** _____



FIXTURE FEATURES

- EACH FIXTURE THERMALLY TESTED TO INSURE LONGEVITY
- MAXIMUM LIGHT DISTRIBUTION THROUGHOUT LENS
- OVER CURRENT, OVER VOLTAGE, SHORT CIRCUIT PROTECTION

BASE: CAST ALUMINUM
 MOUNTS TO ELECTRICAL BOX BY KEY SLOTS OR CENTER NIPPLE

FINISH: BLACK

LENS: WHITE ACRYLIC
 UV STABILIZER, NON

KELVIN: 3000K **CRI:** 80

POWER FACTOR: NORMAL

VOLTAGE: 120V-60HZ

COMPLIANCE: UL LISTED
 WET LOCATION

MIA: MADE IN AMERICA

LED LIGHT SOURCE

- LG / NICHIA BRAND LED CHIPS
- CONSTANT CURRENT DESIGN
 AVERAGE 90 (LPW)
 LUMENS PER WATT
 AT MODULE EFFICACY
- TRIAC OR ELV DIMMING DOWN TO 5 %
 WITH MOST STANDARD TRIAC OR (ELV) ELECTRONIC LOW VOLTAGE
 WALL BOX DIMMERS
- DRIVER : UL LISTED
- MODULE : CSA LISTED
- LM80 & LM82 TESTED
- ROHS COMPLIANT
- LIFE HOURS : 50,000
- WARRANTY : LIMITED 5 YEARS

SYSTEM WATTAGE	LED ENGINE LUMENS					LED CHIPS PER MODULE	LEGACY 30K SUBSTITUTE
	2700K	3000K	3500K	4000K	5000K		
8.8	919	958	986	1005	1044	28	CFL 13
10	1051	1095	1127	1149	1193	32	CFL 18
11.3	1099	1145	1179	1202	1248	36	CFL 2 x 13
12.5	1147	1195	1242	1254	1302	40	CFL 26

SPECIAL OPTIONS

DRIVER

- DV 120 / 277
(NON DIMMABLE)
- DVD 120 / 277
(0-10 VOLT DIMMABLE)

KELVIN

- 2700K
- 3500K
- 4000K
- 5000K

FINISH

- FB - BLACK
- FBZ - BRONZETONE
- FCU - CUSTOM
- FSN - SATIN CHROME
- FW - WHITE

LENS

-
-
-
-
-

ACCESSORIES

- EBA - EXTENDED BASE
- FUS - FUSE
- IB - INDIVIDUAL BOX
- IPC- PHOTO CONTROL
- PCH - PULL CHAIN
- TP - TAMPER SCREWS
-

SIZE

-
-
-
-

TECHNOLOGY

- EMG - EMERGENCY
- EMGR- EMERGENCY
REMOTE
- OC - OCCUPANCY
SENSOR

CUSTOM

-
-
-
-

For Additional Accessories and Options Visit www.aslighting.com