




Fixture specification



MODEL # : **BCG**

STYLE / WATTAGE / KELVIN / FINISH / LENS / ACCESSORIES / SIZE / COMPLIANCE

PROJECT : _____ TYPE : _____ NOTE : _____



FIXTURE FEATURES

- EACH FIXTURE THERMALLY TESTED TO INSURE LONGEVITY
- MAXIMUM LIGHT DISTRIBUTION THROUGHOUT LENS
- OVER CURRENT, OVER VOLTAGE, SHORT CIRCUIT PROTECTION

BASE: C.R. STEEL CONSTRUCTION

MOUNTS TO ELECTRICAL BOX WITH CENTER NIPPLE

FINISH: OIL RUBBED BRONZE

LENS: AMBER GLASS

UV STABILIZED
NON-YELLOWING

POWER FACTOR: HIGH

INPUT VOLTAGE: 120V/50/60Hz

COMPLIANCE: UL AND/OR CSA LISTED

KELVIN: 3000

CRI: 80

MADE IN AMERICA

DAMP LOCATION

LED LIGHT SOURCE

- LG / NICHIA BRAND LED CHIPS
- CONSTANT CURRENT DESIGNN AVERAGE 100 - 120LPM (LUMEN PER WATT) AT MODULE EFFICACY

- TRIAC OR ELECTRONIC LOW VOLTAGE DIMMING DOWN TO 5% WITH WALL BOX DIMMERS

- DRIVER: UL LISTED
- MODULE: CSA LISTED

- LM80 & LM82 TESTED
- ROHS COMPLIANT
- LIFE HOURS: 50,000
- WARRAANTY: LIMITED 5 YEARS

SYSTEM WATTAGE	LED ENGINE LUMENS					LEGACY 30K SUBSTITUTE
	2700K	3000K	3500K	4000K	5000K	
10 / 12 DRIVERLESS		1000 / 800		1000 / 800		CFL 13
15 DRIVERLESS		1200 / 1500		1200 / 1500		CFL 2 x 13
22 / 25 DRIVERLESS		1800 / 2500		1800 / 2500		CFL 3 x 13
8.8	919	958	986	1005	1044	CFL 13
10	1051	1095	1127	1149	1193	CFL 18
11.3	1099	1145	1179	1202	1248	CFL 2 x 13
12.5	1147	1195	1242	1254	1302	CFL 26

SPECIAL OPTIONS

DRIVER

- DV 120 / 277 (NON DIMMABLE)
- DVD 120 / 277 (0-10V DIMMABLE)
- EMG EMERGENCY
- EMGR EMERGENCY REMOTE

FINISH

- FCU CUSTOM (ANY FINISH AVAILABLE)

KELVIN

- 2700K
- 3500K
- 4000K
- 5000K

LENS

- OG OPAL GLASS

COMPLIANCE

- ES ENERGY STAR (WHEN SPECIFIED)

ACCESSORIES

- FUS FUSE
- IB INDIVIDUAL BOX
- OC OCCUPANCY SENSOR
- SP SURGE PROTECTOR

For Additional Accessories and Options Visit www.aslighting.com

ASL
25 Twelfth Street
Brooklyn, NY 11215-3820

Toll Free
Phone: 800-369-1101
Fax: 800-552-3465



Local
Phone: 718-369-1100
Fax: 718-369-1105

Online
email: info@aslighting.com
visit: www.aslighting.com

BCG