




# Fixture Specification

MODEL # **CGE LED**

STYLE / LIGHT SOURCE / WATTAGE / KELVIN / DRIVER / FINISH / LENS / ACCESSORIES / SIZE / COMPLIANCE / DETAIL



PROJECT : \_\_\_\_\_ TYPE : \_\_\_\_\_ NOTE : \_\_\_\_\_



**FIXTURE FEATURES**

- EACH FIXTURE THERMALLY TESTED TO INSURE LONGEVITY
- MAXIMUM LIGHT DISTRIBUTION THROUGHOUT LENS
- OVER CURRENT, OVER VOLTAGE, SHORT CIRCUIT PROTECTION

**HOUSING**

Die Cast Aluminum Base  
 Extended Bases Have Four Threaded and Plugged Conduit Entries  
 Molded Polycarbonate Guard with Gasketed and Tamper Proof Screws  
 Mounts over Electric Box

**LENS**

Frosted Ribbed Polycarbonate  
 UV Stabilized  
 Non Yellowing

**KELVIN:** 3000K **CRI:** 80  
**POWER FACTOR:** NORMAL  
**VOLTAGE:** 120V-60HZ  
**COMPLIANCE:** UL AND OR CSA LISTED WET LOCATION  
**MIA:** MADE IN AMERICA

**LED LIGHT SOURCE**

- LG / NICHIA BRAND LED CHIPS
- CONSTANT CURRENT DESIGN AVERAGE 100 - 120 (LPW) LUMENS PER WATT AT MODULE EFFICACY
- TRIAC OR ELV DIMMING DOWN TO 5 % WITH MOST STANDARD TRIAC OR ( ELV ) ELECTRONIC LOW VOLTAGE WALL BOX DIMMERS / 120V
- DRIVER : UL LISTED
- MODULE : CSA LISTED
- LM80 & LM82 TESTED
- ROHS COMPLIANT
- LIFE HOURS : 50,000
- WARRANTY : LIMITED 5 YEARS

SYSTEM WATTAGE	LED ENGINE LUMENS					LED'S PER MODULE	SMALLEST COMPATIBLE SIZE	LEGACY 30K SUBSTITUTE
	2700K	3000K	3500K	4000K	5000K			
10	1062	1095	1160	1171	1193	32		CFL 18
12.5	1159	1195	1266	1278	1302	40		CFL 2 x 13 / 26
18.8	1799	1855	1966	1984	2021	56		CFL 2 x 18 / 32
20.7	1978	2040	2162	2182	2223	64		CFL 3 x 13
22.3	2158	2225	2358	2380	2425	72		CFL 2 x 26
24.5	2313	2385	2528	2551	2599	80		CFL 4 x 13 / 3 x 18

**SPECIAL OPTIONS**

DRIVER

- DV 120 / 277 (NON DIMMABLE)
- DVD 120 / 277 (0-10 VOLT DIMMABLE)

KELVIN

- 2700K
- 3500K
- 4000K
- 5000K

FINISH

- FB - BLACK
- FBZ - BRONZETONE
- FCU - CUSTOM
- FSN - SATIN NICKEL
- FW - WHITE

LENS

- 
- 
- 
- 

ACCESSORIES

- EBA - EXTENDED BASE
- FUS - FUSE
- IB - INDIVIDUAL BOX
- PCH - PULL CHAIN
- PCK - PENDANT / CANOPY
- TP - TAMPER SCREWS

SIZE

- |                          |         |          |          |
|--------------------------|---------|----------|----------|
|                          | Width   | Height   | Depth    |
| <input type="checkbox"/> | 9-3/16" | 13-1/16" | 4"       |
| <input type="checkbox"/> | 9-3/16" | 13-1/16" | 6-15/32" |
| <input type="checkbox"/> | 9-3/16" | 13-1/16" | 7-13/16" |
| <input type="checkbox"/> |         |          |          |

TECHNOLOGY

- EMG - EMERGENCY
- EMGR- EMERGENCY REMOTE
- OC - OCCUPANCY SENSOR
- IPC- PHOTOCCELL

CUSTOM

- 
- 
- 
- 

For Additional Accessories and Options Visit [www.aslighting.com](http://www.aslighting.com)

ASL  
 25 Twelfth Street  
 Brooklyn, NY 11215-3820

Toll Free  
 Phone: 800-369-1101  
 Fax: 800-552-3465

Local  
 Phone: 718-369-1100  
 Fax: 718-369-1105

Online  
 email: [Info@aslighting.com](mailto:Info@aslighting.com)  
 visit: [www.aslighting.com](http://www.aslighting.com)