




Fixture Specification

MODEL #: **CGM**

STYLE / LAMP / LAMP / WATTAGE / KELVIN / BALLAST / FINISH / LENS / ACCESSORIES / SIZE / COMPLIANCE
 QTY TYPE DETAIL



PROJECT : _____ TYPE : _____ NOTE : _____



FIXTURE FEATURES

- EACH FIXTURE THERMALLY TESTED TO INSURE LONGEVITY
- MAXIMUM LIGHT DISTRIBUTION THROUGHOUT LENS
- OVER CURRENT, OVER VOLTAGE, SHORT CIRCUIT PROTECTION

BASE: DIE CAST ALUMINUM

THREE 1/2" NPT PLUGGED OUTLETS FOR CONDUIT AND/OR PHOTO CELL

MOUNTS TO ELECTRICAL BOX WITH CENTER NIPPLE

FINISH: TEXTURED BLACK

LENS: MILKY WHITE POLYCARBONATE
 UV STABILIZED
 NON-YELLOWING

SECURED BY FOUR STAINLESS STEEL SCREWS

POWER FACTOR: HIGH
 INPUT VOLTAGE: 120V/50/60Hz
 COMPLIANCE: CSA LISTED
 KELVIN: 3000
 CRI: 80

MADE IN AMERICA
 DAMP LOCATION

LED LIGHT SOURCE

- LG / NICHIA BRAND LED CHIPS
- CONSTANT CURRENT DESIGNN AVERAGE 100 - 120LPM (LUMEN PER WATT) AT MODULE EFFICACY
- TRIAC OR ELECTRONIC LOW VOLTAGE DIMMING DOWN TO 5% WITH WALL BOX DIMMERS
- DRIVER: UL LISTED
- MODULE: CSA LISTED
- LM80 & LM82 TESTED
- ROHS COMPLIANT
- LIFE HOURS: 50,000
- WARRAANTY: LIMITED 5 YEARS

SYSTEM WATTAGE	LED ENGINE LUMENS					LEGACY 30K SUBSTITUTE
	2700K	3000K	3500K	4000K	5000K	
10 / 12 DRIVERLESS		1000 / 800		1000 / 800		CFL 13
15 DRIVERLESS		1200 / 1500		1200 / 1500		CFL 2 x 13
22 / 25 DRIVERLESS		1800 / 2500		1800 / 2500		CFL 3 x 13
10	1062	1095	1160	1171	1193	CFL 18
12.5	1159	1195	1266	1278	1302	CFL 2 x 13
19	1799	1855	1966	1984	2021	CFL 2 x 18
21	1978	2040	2162	2182	2223	CFL 3 x 13
22.3	2158	2225	2358	2380	2425	CFL 2 x 26
25	2600	2867	3000	3022	3067	CFL 2 x 32
38	3700	3867	4000	4022	4067	CFL 4 x 26

SPECIAL OPTIONS

- DRIVER**
- DV 120 / 277 (NON DIMMABLE)
 - DVD 120 / 277 (0-10V DIMMABLE)
 - EMG EMERGENCY
 - EMGR EMERGENCY REMOTE

- FINISH**
- FCU CUSTOM (ANY FINISH AVAILABLE)
 - FW WHITE

- COMPLIANCE**
- ES ENERGY STAR (WHEN SPECIFIED)

- KELVIN**
- 2700K
 - 3500K
 - 4000K
 - 5000K

- ACCESSORIES**
- EPC EXTERNAL PHOTOCELL
 - FUS FUSE
 - IB INDIVIDUAL BOX
 - OC OCCUPANCY SENSOR
 - SP SURGE PROTECTOR

For Additional Accessories and Options Visit www.aslighting.com

ASL
 25 Twelfth Street
 Brooklyn, NY 11215-3820

Toll Free
 Phone: 800-369-1101
 Fax: 800-552-3465



Local
 Phone: 718-369-1100
 Fax: 718-369-1105

Online
 email: info@aslighting.com
 visit: www.aslighting.com

