




# Fixture Specification

MODEL #: **DREC**

STYLE / LAMP / LAMP / WATTAGE / KELVIN / BALLAST / FINISH / LENS / ACCESSORIES / SIZE / COMPLIANCE  
 QTY TYPE TYPE DETAIL



PROJECT : \_\_\_\_\_ TYPE : \_\_\_\_\_ NOTE : \_\_\_\_\_



**FIXTURE FEATURES**

- EACH FIXTURE THERMALLY TESTED TO INSURE LONGEVITY
- MAXIMUM LIGHT DISTRIBUTION THROUGHOUT LENS
- OVER CURRENT, OVER VOLTAGE, SHORT CIRCUIT PROTECTION

BASE: INJECTION MOLDED POLYCARBONATE  
 MOUNTS TO ELECTRICAL BOX WITH CENTER NIPPLE  
 FINISH: BLACK  
 LENS: CLEAR PRISMATIC POLYCARBONATE  
 UV STABILIZED  
 NON-YELLOWING

POWER FACTOR: HIGH  
 INPUT VOLTAGE: 120V/50/60Hz  
 COMPLIANCE: UL AND/OR CSA LISTED  
 KELVIN: 3000  
 CRI: 80  
 MADE IN AMERICA  
 WET LOCATION

**LED LIGHT SOURCE**

- LG / NICHIA BRAND LED CHIPS
- CONSTANT CURRENT DESIGNN AVERAGE 100 - 120LPM ( LUMEN PER WATT ) AT MODULE EFFICACY
- TRIAC OR ELECTRONIC LOW VOLTAGE DIMMING DOWN TO 5% WITH WALL BOX DIMMERS
- DRIVER: UL LISTED
- MODULE: CSA LISTED
- LM80 & LM82 TESTED
- ROHS COMPLIANT
- LIFE HOURS: 50,000
- WARRAANTY: LIMITED 5 YEARS

SYSTEM WATTAGE	LED ENGINE LUMENS					LEGACY 30K SUBSTITUTE
	2700K	3000K	3500K	4000K	5000K	
10 / 12 DRIVERLESS		1000 / 800		1000 / 800		CFL 13
15 DRIVERLESS		1200 / 1500		1200 / 1500		CFL 2 x 13
22 / 25 DRIVERLESS		1800 / 2500		1800 / 2500		CFL 3 x 13
8.8	919	958	986	1005	1044	CFL 13
10	1051	1095	1127	1149	1193	CFL 18
11.3	1099	1145	1179	1202	1248	CFL 2 x 13
12.5	1147	1195	1242	1254	1302	CFL 26

**SPECIAL OPTIONS**

- DRIVER**
- DV 120 / 277 (NON DIMMABLE)
  - DVD 120 / 277 (0-10V DIMMABLE)
  - EMG EMERGENCY
  - EMGR EMERGENCY REMOTE

- FINISH**
- FW WHITE
- KELVIN**
- 2700K
  - 3500K
  - 4000K
  - 5000K

- LENS**
- WP WHITE POLYCARBONATE
- COMPLIANCE**
- ES ENERGY STAR (WHEN SPECIFIED)

- ACCESSORIES**
- EPC EXTERNAL PHOTOCELL
  - FUS FUSE
  - IB INDIVIDUAL BOX
  - IPC INTERNAL PHOTOCELL
  - OC OCCUPANCY SENSOR
  - SP SURGE PROTECTOR

For Additional Accessories and Options Visit [www.aslighting.com](http://www.aslighting.com)

ASL  
 25 Twelfth Street  
 Brooklyn, NY 11215-3820

Toll Free  
 Phone: 800-369-1101  
 Fax: 800-552-3465



Local  
 Phone: 718-369-1100  
 Fax: 718-369-1105

Online  
 email: [info@aslighting.com](mailto:info@aslighting.com)  
 visit: [www.aslighting.com](http://www.aslighting.com)

**DREC**