



Fixture specification

MODEL NUMBER: **ICH** JOB: _____ TYPE: _____



Light Source

Type	Twin Tube						Linear						Length	Width	Height	
	13	18	24	36	40	55	T8			T5 HO						
Wattage	3	2	1/2	1	-	-	15	17	25	32	24	39	54	24-1/4"	4-1/2"	4-3/8"
Quantity	-	-	2	-	-	-	-	1/2	-	-	1/2	-	1	36-1/4"	4-1/2"	4-3/8"
	-	-	-	2	-	-	-	-	-	1/2	-	-	1	48-1/4"	4-1/2"	4-3/8"

Standard Features

BASE	Die Formed Steel Knockouts for Optional Convenience Outlet and/or Switch Mounts with Holes and Knockouts Provided	FINISH	White	LENS	Clear Prismatic Polycarbonate UV Stabilized Non Yellowing Mounted by Tongue / Groove Fit and and Secured with End Caps and Two White Acorn Cap Nuts
LAMP	Twin - 2700K Linear - 4100K	TECHNOLOGY	Electronic Ballast Normal Power Factor 120V-60Hz AC UL Listed Damp Location		

Special options

Please Note: Standard Features May Change if Fixtures are Ordered with Special Option(s).

BALLAST	<input type="checkbox"/> DV 120/277 <input type="checkbox"/> EBD Dimmable <input type="checkbox"/> EMG Emergency <input type="checkbox"/> HPF High Power Factor <input type="checkbox"/> V 277 Volt	ACCESSORIES	<input type="checkbox"/> CO Convenience Outlet <input type="checkbox"/> PCH Pull Chain Switch <input type="checkbox"/> PS Pin Switch <input type="checkbox"/> RS Rocker Switch	LENS	<input type="checkbox"/> WP White Polycarbonate
KELVIN	<input type="checkbox"/> 3500K <input type="checkbox"/> 4100K	COMPLIANCE	<input type="checkbox"/> ES www.energystar.gov for Qualified Models		For Accessories and Adders See Catalog Page 79

ASL
25 Twelfth Street
Brooklyn, NY 11215-3820

Toll Free
Phone: 800-369-1101
Fax: 800-552-3465

Local
Phone: 718-369-1100
Fax: 718-369-1105

Online
email: info@asllighting.com
visit: www.asllighting.com

