




Fixture Specification

MODEL # **INS LED**

STYLE / LIGHT SOURCE / WATTAGE / KELVIN / DRIVER / FINISH / LENS / ACCESSORIES / SIZE / COMPLIANCE / DETAIL



PROJECT : _____ TYPE : _____ NOTE : _____



FIXTURE FEATURES

- EACH FIXTURE THERMALLY TESTED TO INSURE LONGEVITY
- MAXIMUM LIGHT DISTRIBUTION THROUGHOUT LENS
- OVER CURRENT, OVER VOLTAGE, SHORT CIRCUIT PROTECTION

BASE: ALUMINUM CONSTRUCT MOUNTS TO ELECTRICAL BOX BY KEY SLOTS OR CENTER NIPPLE

FINISH: WHITE

LENS: CLEAR PRISMATIC POLY

KELVIN: 3000K **CRI:** 80

POWER FACTOR: NORMAL

VOLTAGE: 120V-60HZ

COMPLIANCE: UL LISTED DAMP LOCATION

MIA: MADE IN AMERICA

LED LIGHT SOURCE

- LG / NICHIA BRAND LED CHIPS
- CONSTANT CURRENT DESIGN AVERAGE 100 - 120 (LPW) LUMENS PER WATT AT MODULE EFFICACY
- TRIAC OR ELV DIMMING DOWN TO 5 % WITH MOST STANDARD TRIAC OR (ELV) ELECTRONIC LOW VOLTAGE WALL BOX DIMMERS / 120V
- DRIVER : UL LISTED
- MODULE : CSA LISTED
- LM80 & LM82 TESTED
- ROHS COMPLIANT
- LIFE HOURS : 50,000
- WARRANTY : LIMITED 5 YEARS

SYSTEM WATTAGE	LED ENGINE LUMENS					LED CHIPS PER	MAXIMUM SIZE	LEGACY 30K SUBSTITUTE
	2700K	3000K	3500K	4000K	5000K			
10	1062	1095	1160	1171	1193	32		CFL 18
12.5	1159	1195	1266	1278	1302	40		CFL 2 x 13 / 26
18.8	1799	1855	1966	1984	2021	56		CFL 2 x 18 / 32
20.7	1978	2040	2162	2182	2223	64		CFL 3 x 13
22.3	2158	2225	2358	2380	2425	72		CFL 2 x 26
24.5	2313	2385	2528	2551	2599	80		CFL 4 x 13 / 3 x 18

SPECIAL OPTIONS

DRIVER

- DV 120 / 277 (NON DIMMABLE)
- DVD 120 / 277 (0-10 VOLT DIMMABLE)

KELVIN

- 2700K
- 3500K
- 4000K
- 5000K

FINISH

- FB - BLACK
- FBZ - BRONZETONE
- FCU - CUSTOM
- FSN - SATIN NICKEL
- FW - WHITE

LENS

- WHITE POLY
-
-
-

ACCESSORIES

- EBA - EXTENDED BASE
- FUS - FUSE
- IB - INDIVIDUAL BOX
- PCH - PULL CHAIN
- PCK - PENDANT / CANOPY
- TP - TAMPER SCREWS

SIZE

- S: 8-5/8" H: 4-1/2"
- S: 12" H: 5-1/4"
-
-

TECHNOLOGY

- EMG - EMERGENCY
- EMGR- EMERGENCY REMOTE
- OC - OCCUPANCY SENSOR

CUSTOM

-
-
-
-

For Additional Accessories and Options Visit www.aslighting.com