




# Fixture Specification

MODEL # **BSV LED**  
 STYLE / LIGHT / WATTAGE / KELVIN / DRIVER / FINISH / LENS / ACCESSORIES / SIZE / COMPLIANCE  
 SOURCE / DETAIL



PROJECT : \_\_\_\_\_ TYPE : \_\_\_\_\_ NOTE : \_\_\_\_\_



### FIXTURE FEATURES

- EACH FIXTURE THERMALLY TESTED TO INSURE LONGEVITY
- MAXIMUM LIGHT DISTRIBUTION THROUGHOUT LENS
- OVER CURRENT, OVER VOLTAGE, SHORT CIRCUIT PROTECTION

**BASE:** STEEL CONSTRUCTION  
 MOUNTS TO ELECTRICAL BOX BY KEY SLOTS OR CENTER NIPPLE

**FINISH:** OIL BRONZE

**LENS:** FROSTED MILK GLASS

**KELVIN:** 3000K **CRI:** 80

**POWER FACTOR:** NORMAL

**VOLTAGE:** 120V-60HZ

**COMPLIANCE:** UL LISTED  
**Wet Location**

**MIA:** MADE IN AMERICA

### LED LIGHT SOURCE

- LG / NICHIA BRAND LED CHIPS
- CONSTANT CURRENT DESIGN AVERAGE 90 ( LPW ) LUMENS PER WATT AT MODULE EFFICACY
- TRIAC OR ELV DIMMING DOWN TO 5 % WITH MOST STANDARD TRIAC OR ( ELV ) ELECTRONIC LOW VOLTAGE WALL BOX DIMMERS
- DRIVER : UL LISTED
- MODULE : CSA LISTED
- LM80 & LM82 TESTED
- ROHS COMPLIANT
- LIFE HOURS : 50,000
- WARRANTY : LIMITED 5 YEARS

SYSTEM WATTAGE	LED ENGINE LUMENS					LED CHIPS PER MODULE	LEGACY 30K SUBSTITUTE
	2700K	3000K	3500K	4000K	5000K		
8.8	919	958	986	1005	1044	28	CFL 13
10	1051	1095	1127	1149	1193	32	CFL 18
11.3	1099	1145	1179	1202	1248	36	CFL 2 x 13
12.5	1147	1195	1242	1254	1302	40	CFL 26

### SPECIAL OPTIONS

#### DRIVER

- DV 120 / 277 (NON DIMMABLE)
- DVD 120 / 277 (0-10 VOLT DIMMABLE)

#### KELVIN

- 2700K
- 3500K
- 4000K
- 5000K

#### FINISH

- FB - BLACK
- FBZ - BRONZETONE
- FCU - CUSTOM
- FSN - SATIN NICKEL
- FW - WHITE

#### LENS

- 
- 
- 
- 
- 

#### ACCESSORIES

- EBA - EXTENDED BASE
- FUS - FUSE
- IB - INDIVIDUAL BOX
- IPC- PHOTO CONTROL
- PCH - PULL CHAIN
- TP - TAMPER SCREWS
- 

#### SIZE

- 
- 
- 
- 

#### TECHNOLOGY

- EMG - EMERGENCY
- EMGR- EMERGENCY REMOTE
- OC - OCCUPANCY SENSOR

#### CUSTOM

- 
- 
- 
- 

For Additional Accessories and Options Visit [www.aslighting.com](http://www.aslighting.com)