




Fixture Specification

MODEL #: TSD

STYLE / LAMP / LAMP / WATTAGE / KELVIN / BALLAST / FINISH / LENS / ACCESSORIES / SIZE / COMPLIANCE
QTY TYPE DETAIL



PROJECT : _____ TYPE : _____ NOTE : _____



Light Source

Type	Twin Tube		Quad, Spiral or Triple			Triple	
Wattage	9	13	13	18	26	32	42
Quantity	2	1/2/3	1/2/3	1/2	1/2	1	1

BASE Die Formed Steel
Mounts to Electric Box by
Pre-Punched Keyhole Slots

FINISH Polished Chrome

LENS Opal White Acrylic
UV Stabilized
Non Yellowing

LAMP Twin, Spiral, Quad,
and Triple - 2700K

TECHNOLOGY Electronic Ballast
Normal Power Factor
120V-60Hz AC
UL Listed
Damp Location

Special options

Please Note: Standard Features May Change if Fixtures are Ordered with Special Option(s).

BALLAST DV 120/277
 EBD Dimmable
 EMG Emergency
 HPF High Power Factor
 V 277 Volt

FINISH FB Black
 FW White

KELVIN 3500K
 4100K

TECHNOLOGY GU24 (Energy Star
Compliant Component)
 LED
 Occupancy Sensor

COMPLIANCE ES Energy Star

MIA Made In America

For Additional Accessories and Options Visit www.aslighting.com

ASL
25 Twelfth Street
Brooklyn, NY 11215-3820

Toll Free
Phone: 800-369-1101
Fax: 800-552-3465

Local
Phone: 718-369-1100
Fax: 718-369-1105

Online
email: info@aslighting.com
visit: www.aslighting.com



© copyright 2008 by American Scientific Lighting Corp. All rights reserved.

TSD